

Eaton 189885

Eaton Moeller® series PKZM01 Motor-protective circuit-breaker (-EA), 440 V: 0.55 kW, I_r = 1 - 1.6 A, IP20

General specifications

PRODUCT NAME	Eaton Moeller® series PKZM01 Motor-protective circuit-breaker
CATALOG NUMBER	189885
EAN	4015081878819
PRODUCT LENGTH/DEPTH	93 mm
PRODUCT HEIGHT	90 mm
PRODUCT WIDTH	45 mm
PRODUCT WEIGHT	0.292 kg
COMPLIANCES	CE Marked RoHS conform
MODEL CODE	PKZM01-1,6-EA

Caracteristici & funcții

ACTUATOR TYPE	Push button
FEATURES	Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102)
FUNCTIONS	Phase failure sensitive
NUMBER OF POLES	Three-pole

Generalități

CONNECTION	Screw terminals
LIFESPAN, ELECTRICAL	50,000 operations (at 400V, AC-3)
LIFESPAN, MECHANICAL	50,000 Operations (Main conducting paths)
MOUNTING POSITION	Can be snapped on to IEC/EN 60715 top-hat rail with 7.5 or 15 mm height.
OPERATING FREQUENCY	40 Operations/h
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Motor protective circuit breaker
PROTECTION	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
SHOCK RESISTANCE	25 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
SUITABLE FOR	Branch circuit: Suitable for group installations, (UL/CSA) Also motors with efficiency class IE3
TEMPERATURE COMPENSATION	-5 - 40 °C to IEC/EN 60947, VDE 0660 -25 - 55 °C, Operating range ≤ 0.25 %/K, residual error for T > 40°

Condiții climatice de mediu

AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Tensiune nominală

RATED FREQUENCY - MIN	50 Hz
RATED FREQUENCY - MAX	60 Hz
RATED OPERATIONAL CURRENT (IE)	1.6 A
RATED OPERATIONAL POWER AT AC-3E, 220/230 V, 50 HZ	0.25 kW
RATED OPERATIONAL POWER AT AC-3E, 380/400 V, 50 HZ	0.55 kW
RATED OPERATIONAL VOLTAGE (UE) - MIN	440 V
RATED OPERATIONAL VOLTAGE (UE) - MAX	440 V
RATED UNINTERRUPTED CURRENT (IU)	1.6 A

Capacitatea nominală a motorului

ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 1-PHASE	0.1 HP
ASSIGNED MOTOR POWER AT 460/480 V, 60 HZ, 3-PHASE	0.75 HP
ASSIGNED MOTOR POWER AT 575/600 V, 60 HZ, 3-PHASE	0.75 HP

Secțiuni de racordare

TERMINAL CAPACITY (SOLID)	1 x (1 - 6) mm ² 2 x (1 - 6) mm ²
TERMINAL CAPACITY (SOLID/STRANDED AWG)	18 - 10
STRIPPING LENGTH (MAIN CABLE)	10 mm
TIGHTENING TORQUE	1.7 Nm, Screw terminals, Main cable

Grad de protecție la scurtcircuit

SHORT-CIRCUIT CURRENT RATING (GROUP PROTECTION)	50 kA, 600 V High Fault, Fuse, SCCR (UL/CSA) with 600 A, 600 V High Fault, Fuse, SCCR (UL/CSA) 50 kA, 600 V High Fault, CB, SCCR (UL/CSA) with 600 A, 600 V High Fault, CB, SCCR (UL/CSA)
SHORT-CIRCUIT RELEASE	Basic device fixed 15.5 x I _u ± 20% tolerance 24.8 A, I _{rm}
RATED SHORT-CIRCUIT BREAKING CAPACITY ICS AT 400 V AC	50 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY ICU AT 400 V AC	50 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY ICU AT 440 V AC	50 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY ICS AT 440 V AC	50 kA

Bloc de declanșare

OVERLOAD RELEASE CURRENT SETTING - MIN	1 A
OVERLOAD RELEASE CURRENT SETTING - MAX	1.6 A

Verificarea proiectării

EQUIPMENT HEAT
DISSIPATION, CURRENT-
DEPENDENT PVID 5.36 W

HEAT DISSIPATION
CAPACITY PDISS 0 W

HEAT DISSIPATION PER
POLE, CURRENT-
DEPENDENT PVID 1.8 W

RATED OPERATIONAL
CURRENT FOR SPECIFIED
HEAT DISSIPATION (IN) 1.6 A

STATIC HEAT
DISSIPATION, NON-
CURRENT-DEPENDENT
PVS 0 W

Resurse

CHARACTERISTIC CURVE [eaton-manual-motor-starters-characteristic-characteristic-curve-006.eps](#)

[eaton-manual-motor-starters-characteristic-characteristic-curve-008.eps](#)

DECLARATIONS OF
CONFORMITY [eaton-motor-protective-circuit-breaker-declaration-of-conformity-uk251169en.pdf](#)

INSTRUCȚIUNI DE
INSTALARE [IL034045ZU](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATA:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Irlanda
Eaton.com

© 2025 Eaton. Toate drepturile rezervate

Follow us on social media to get the latest product and support information.

