

Imaginile sunt doar cu titlu informativ

Eaton 189905

Eaton Moeller® series PKZM0 Motor-protective circuit-breaker (-EA), 3p, Ir=10-16A, screw connection

General specifications

PRODUCT NAME	Eaton Moeller® series PKZM0 Motor-protective circuit-breaker
CATALOG NUMBER	189905
EAN	4015081879014
PRODUCT LENGTH/DEPTH	76 mm
PRODUCT HEIGHT	93 mm
PRODUCT WIDTH	45 mm
PRODUCT WEIGHT	0.292 kg
COMPLIANCES	RoHS conform CE Marked
MODEL CODE	PKZM0-16-EA

Caracteristici & funcții

ACTUATOR TYPE	Turn button
FEATURES	Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102)
FUNCTIONS	Phase failure sensitive
NUMBER OF POLES	Three-pole

Generalități

CONNECTION	Screw terminals
LIFESPAN, ELECTRICAL	100,000 operations
LIFESPAN, MECHANICAL	100,000 Operations
MOUNTING POSITION	Can be snapped on to IEC/EN 60715 top-hat rail with 7.5 or 15 mm height.
OPERATING FREQUENCY	40 Operations/h
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Motor protective circuit breaker
PROTECTION	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
SHOCK RESISTANCE	25 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
SUITABLE FOR	Branch circuit: Suitable for group installations, (UL/CSA) Also motors with efficiency class IE3
TEMPERATURE COMPENSATION	-5 - 40 °C to IEC/EN 60947, VDE 0660 -25 - 55 °C, Operating range ≤ 0.25 %/K, residual error for T > 40°

Condiții climatice de mediu

AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78

Secțiuni de racordare

TERMINAL CAPACITY (SOLID)	1 x (1 - 6) mm ² 2 x (1 - 6) mm ²
TERMINAL CAPACITY (SOLID/STRANDED AWG)	18 - 10
STRIPPING LENGTH (MAIN CABLE)	10 mm
TIGHTENING TORQUE	1.7 Nm, Screw terminals, Main cable

Tensiune nominală

RATED FREQUENCY - MIN 50 Hz

RATED FREQUENCY - MAX 60 Hz

RATED OPERATIONAL CURRENT (IE) 16 A

RATED OPERATIONAL POWER AT AC-3E, 220/230 V, 50 HZ 4 kW

RATED OPERATIONAL POWER AT AC-3E, 380/400 V, 50 HZ 7.5 kW

RATED OPERATIONAL VOLTAGE (UE) - MIN 690 V

RATED OPERATIONAL VOLTAGE (UE) - MAX 690 V

RATED UNINTERRUPTED CURRENT (IU) 16 A

Grad de protecție la scurtcircuit

10 kA, 600 V High Fault, Fuse, SCCR (UL/CSA) with 150 A, 600 V High Fault, Fuse, SCCR (UL/CSA)
 10 kA, 600 V High Fault, CB, SCCR (UL/CSA) with 125 A, 600 V High Fault, CB, SCCR (UL/CSA)
 50 kA, 600 V High Fault, CB with CL, SCCR (UL/CSA) with 600 A, 600 V High Fault, CB with CL, SCCR (UL/CSA)
 50 kA, 600 V High Fault, Fuse with CL, SCCR (UL/CSA) with 600 A, 600 V High Fault, Fuse with CL, SCCR (UL/CSA)
 18 kA, 480 V High Fault, CB, SCCR (UL/CSA) with 600 A, 480 V High Fault, CB, SCCR (UL/CSA)
 18 kA, 480 V High Fault, Fuse, SCCR (UL/CSA) with 600 A, 480 V High Fault, Fuse, SCCR (UL/CSA)

SHORT-CIRCUIT CURRENT RATING (GROUP PROTECTION)

SHORT-CIRCUIT RELEASE Basic device fixed 15.5 x I_u
 ± 20% tolerance
 248 A, I_{rm}

RATED SHORT-CIRCUIT BREAKING CAPACITY ICS AT 400 V AC 38 kA

RATED SHORT-CIRCUIT BREAKING CAPACITY ICU AT 400 V AC 50 kA

RATED SHORT-CIRCUIT BREAKING CAPACITY ICU AT 440 V AC 15 kA

RATED SHORT-CIRCUIT BREAKING CAPACITY ICS AT 440 V AC 12 kA

RATED SHORT-CIRCUIT BREAKING CAPACITY ICU AT 500 V AC 15 kA

RATED SHORT-CIRCUIT BREAKING CAPACITY ICS AT 500 V AC 4 kA

RATED SHORT-CIRCUIT BREAKING CAPACITY ICU AT 690 V AC 3 kA

RATED SHORT-CIRCUIT BREAKING CAPACITY ICS AT 690 V AC 2 kA

Capacitatea nominală a motorului

ASSIGNED MOTOR
POWER AT 230/240 V, 60 HZ, 1-PHASE 2 HP

ASSIGNED MOTOR
POWER AT 230/240 V, 60 HZ, 3-PHASE 5 HP

ASSIGNED MOTOR
POWER AT 460/480 V, 60 HZ, 3-PHASE 10 HP

ASSIGNED MOTOR
POWER AT 575/600 V, 60 HZ, 3-PHASE 10 HP

Verificarea proiectării

EQUIPMENT HEAT
DISSIPATION, CURRENT-
DEPENDENT PVID 6.43 W

HEAT DISSIPATION
CAPACITY PDISS 0 W

HEAT DISSIPATION PER
POLE, CURRENT-
DEPENDENT PVID 2.1 W

RATED OPERATIONAL
CURRENT FOR SPECIFIED
HEAT DISSIPATION (IN) 16 A

STATIC HEAT
DISSIPATION, NON-
CURRENT-DEPENDENT
PVS 0 W

Bloc de declanșare

OVERLOAD RELEASE
CURRENT SETTING - MIN 10 A

OVERLOAD RELEASE
CURRENT SETTING - MAX 16 A

Resurse

CHARACTERISTIC CURVE [eaton-manual-motor-starters-pkz-characteristic-curve-002.eps](#)

CHARACTERISTIC CURVE [eaton-manual-motor-starters-characteristic-characteristic-curve-008.eps](#)

DECLARATIONS OF
CONFORMITY [eaton-motor-protective-circuit-breaker-declaration-of-conformity-uk251169en.pdf](#)

DESENE [eaton-manual-motor-starters-circuit-breaker-pkzm0-3d-drawing.eps](#)

DESENE [eaton-manual-motor-starters-pkzm0-3d-drawing-008.eps](#)

INSTRUCȚIUNI DE
INSTALARE [IL034046ZU](#)

SCHEME ELECTRICE [eaton-manual-motor-starters-transformer-pkzm0-wiring-diagram.eps](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATA:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Irlanda
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. Toate drepturile rezervate