

Specifications



Eaton 194730

Eaton Moeller series xPole - HL/HL-HX MCB.
HL, xPole Home, 1-pole, tripping
characteristic: C, rated current I_n: 13 A, rated
switching capacity IEC/EN 60898-1: 4,5 kA

General specifications

| | |
|-----------------------------|---|
| PRODUCT NAME | Eaton Moeller series xPole - HL/HL-HX MCB |
| CATALOG NUMBER | 194730 |
| MODEL CODE | HL-C13/1 |
| EAN | 9010238062146 |
| PRODUCT LENGTH/DEPTH | 85 mm |
| PRODUCT HEIGHT | 73 mm |
| PRODUCT WIDTH | 17.5 mm |
| PRODUCT WEIGHT | 0.12 kg |
| COMPLIANCES | RoHS conform |
| GLOBAL CATALOG | 194730 |



Powering Business Worldwide

Product specifications

| | |
|---|--|
| USED WITH | HL Miniature circuit breaker |
| AMPERAGE RATING | 13 A |
| FEATURES | Additional equipment possible |
| 10.10 TEMPERATURE RISE | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 SHORT-CIRCUIT RATING | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 ELECTROMAGNETIC COMPATIBILITY | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 MECHANICAL FUNCTION | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |
| 10.2.2 CORROSION RESISTANCE | Meets the product standard's requirements. |
| 10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES | Meets the product standard's requirements. |
| 10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT | Meets the product standard's requirements. |
| 10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS | Meets the product standard's requirements. |
| 10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION | Meets the product standard's requirements. |
| 10.2.5 LIFTING | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 MECHANICAL IMPACT | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 INSCRIPTIONS | Meets the product standard's requirements. |
| 10.3 DEGREE OF | Does not apply, since the |

Resources

| | |
|-----------------------------------|--|
| BROCHURES | eaton-xPole-home-leaflet-br003019en-en-gb.pdf |
| CATALOGS | eaton-xpole%20home-hl-hx-mcb-catalog-ca019019en-en-us.pdf eaton-xpole%20home-catalog-ca019002en-en-us.pdf |
| CHARACTERISTIC CURVE | eaton-xpole-mmc4-6-m-mcb-characteristic-curve-002.jpg eaton-xpole-mmc4-6-m-mcb-characteristic-curve-004.jpg |
| DECLARATIONS OF CONFORMITY | eaton-mcb-declaration-of-conformity-eu250068en.pdf |
| DRAWINGS | eaton-xpole-pl6-mcb-dimensions.jpg eaton-xpole-hlhl-hx-mcb-3d-drawing-002.jpg pls_1p.dwg |
| MCAD MODEL | eaton-non-selective-universal-mcb-mcad-drawings-faz-pls-1p.dwg pls_1p.stp |
| WIRING DIAGRAMS | eaton-xpole-mmc4-6-m-mcb-wiring-diagram-002.jpg |

| | |
|---|--|
| PROTECTION OF ASSEMBLIES | entire switchgear needs to be evaluated. |
| 10.4 CLEARANCES AND CREEPAGE DISTANCES | Meets the product standard's requirements. |
| 10.5 PROTECTION AGAINST ELECTRIC SHOCK | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS | Is the panel builder's responsibility. |
| 10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS | Is the panel builder's responsibility. |
| 10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH | Is the panel builder's responsibility. |
| 10.9.3 IMPULSE WITHSTAND VOLTAGE | Is the panel builder's responsibility. |
| 10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL | Is the panel builder's responsibility. |
| POLLUTION DEGREE | 3 |
| DEGREE OF PROTECTION | IP20 |
| EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT | 2.5 W |
| RATED IMPULSE WITHSTAND VOLTAGE (UIMP) | 4 kV |
| TRIPPING CHARACTERISTIC | C |
| AMBIENT OPERATING TEMPERATURE - MAX | 75 °C |
| AMBIENT OPERATING TEMPERATURE - MIN | -25 °C |
| BUILT-IN DEPTH | 44 mm |
| CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MAX | 25 mm ² |
| CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MIN | 1 mm ² |
| CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MAX | 25 mm ² |
| CONNECTABLE | 1 mm ² |

| | |
|--|--|
| CONDUCTOR CROSS SECTION (SOLID-CORE) - MIN | |
| CURRENT LIMITING CLASS | 3 |
| FREQUENCY RATING - MAX | 60 Hz |
| FREQUENCY RATING - MIN | 50 Hz |
| HEAT DISSIPATION CAPACITY | 0 W |
| HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT | 0 W |
| WIDTH IN NUMBER OF MODULAR SPACINGS | 1 |
| VOLTAGE TYPE | AC |
| OVERVOLTAGE CATEGORY | III |
| NUMBER OF POLES | Single-pole |
| RELEASE CHARACTERISTIC | C |
| TYPE | <ul style="list-style-type: none"> • HL • Miniature circuit breaker |
| SPECIAL FEATURES | Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity |
| APPLICATION | <ul style="list-style-type: none"> • Switchgear for residential and commercial applications • xPole Home - Switchgear for residential applications |
| NUMBER OF POLES (PROTECTED) | 1 |
| NUMBER OF POLES (TOTAL) | 1 |
| RATED INSULATION VOLTAGE (UI) | 440 V |
| RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) | 13 A |
| RATED OPERATIONAL VOLTAGE (UE) - MAX | 230 V |
| RATED SHORT-CIRCUIT | 4.5 kA |

| | |
|---|----------------------------|
| BREAKING CAPACITY (IEC/EN 60898-1) - ICN AT 230 V | |
| RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC/EN 60898-1)- ICN AT 400 V | 4.5 kA |
| RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2)- ICU AT 230 V | 0 kA |
| RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2)- ICU AT 400 V | 0 kA |
| RATED SWITCHING CAPACITY (IEC/EN 60898- 1) | 4.5 kA |
| STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT | 0 W |
| SUITABLE FOR | Flush-mounted installation |
| POWER LOSS | 2.5 W |

| |
|------------------------|
| PROJECT NAME: |
| PROJECT NUMBER: |
| PREPARED BY: |
| DATE: |



Eaton Corporation plc
 Eaton House
 30 Pembroke Road
 Dublin 4, Ireland
 Eaton.com

Follow us on social media to get the latest product and support information.

