

# Specifications



## Eaton 216374

Eaton Moeller® series M22 Adapter

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller® series M22 Adapter
<b>CATALOG NUMBER</b>	216374
<b>MODEL CODE</b>	M22-A
<b>EAN</b>	4015082163747
<b>PRODUCT LENGTH/DEPTH</b>	10 mm
<b>PRODUCT HEIGHT</b>	41 mm
<b>PRODUCT WIDTH</b>	30 mm
<b>PRODUCT WEIGHT</b>	0.003 kg
<b>CERTIFICATIONS</b>	UL UL 508 UL Category Control No.: NKCR IEC/EN 60947-5 UL File No.: E29184 CSA-C22.2 No. 14-05 CE CSA Class No.: 3211-03 CSA CSA File No.: 012528 CSA-C22.2 No. 94-91
<b>GLOBAL CATALOG</b>	216374



Powering Business Worldwide

## Product specifications

<b>TYPE</b>	Mounting clamp (front mounting) for 3-contact LED elements
<b>10.10 TEMPERATURE RISE</b>	Not applicable.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Please enquire
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.

## Resources

	<a href="#">eaton-rmq-titan-brochure-br047004en-en-us.pdf</a>
	<a href="#">eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf</a>
CATALOGS	<a href="#">Flip catalog - Product Range Catalog - Command and indication</a>
	<a href="#">eaton-operating-adapter-m22-mounting-clamp-dimensions-002.eps</a>
DRAWINGS	<a href="#">eaton-operating-samrtwire-m22-mounting-clamp-3d-drawing.eps</a> <a href="#">eaton-operating-adapter-m22-mounting-clamp-flow-diagram.eps</a>
ECAD MODEL	<a href="#">ETN.216374.edz</a>
FLYERS	<a href="#">eaton-rmq-titan-selection-aid-brochure-fl047002-en-us.pdf</a>
INSTALLATION INSTRUCTIONS	<a href="#">IL04716002Z</a>
INSTALLATION VIDEOS	<a href="#">RMQ Flat Design</a>
	<a href="#">DA-CD-adapter</a>
MCAD MODEL	<a href="#">DA-CS-adapter</a>
	<a href="#">easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator</a>
MULTIMEDIA	<a href="#">MCI Multicolor Light Indicator M22 with SmartWire-DT</a> <a href="#">RMQ small E-Stop emergency-stop button</a> <a href="#">MCI MultiColor Light Indicator RMQ compact solution</a>
PEP ECO-PASSPORT	<a href="#">EATO-00049-V01.01-EN</a>
	<a href="#">eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf</a>
SALES NOTES	<a href="#">eaton-control-circuit-devices-rmq-titan-fl144090en-en-us.pdf</a>

<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>CLIMATIC PROOFING</b>	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
<b>CONNECTION TO SMARTWIRE-DT</b>	Yes
<b>CONNECTION TYPE</b>	Front fixing
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	70 °C
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>BUILT-IN DIAMETER</b>	22 mm
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>	0 W
<b>FORCE FOR POSITIVE OPENING - MIN</b>	0 N
<b>HEAT DISSIPATION CAPACITY PDISS</b>	0 W
<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>	0 W
<b>NUMBER OF APPLIANCES TO BUILD IN</b>	3
<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	0 A
<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>	0 W

[eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf](#)

[eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf](#)

---

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

---



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.