

Specifications



Photo is representative

Eaton 216539

Eaton Moeller® series M22 Surface mounting enclosure, 4 mounting locations

General specifications

PRODUCT NAME	Eaton Moeller® series M22 Accessory Surface mounting enclosure
CATALOG NUMBER	216539
MODEL CODE	M22-I4
EAN	4015082165390
PRODUCT LENGTH/DEPTH	80 mm
PRODUCT HEIGHT	56 mm
PRODUCT WIDTH	186 mm
PRODUCT WEIGHT	0.279 kg
CERTIFICATIONS	CSA-C22.2 No. 14-05 UL 508 CSA Class No.: 3211-03 CSA CSA File No.: 012528 CSA-C22.2 No. 94-91 UL UL Category Control No.: NKCR CE UL File No.: E29184 IEC/EN 60947-5
GLOBAL CATALOG	216539



Powering Business Worldwide

Product specifications

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION	Does not apply, since the

Resources

	Flip catalog - Product Range Catalog - Command and indication eaton-rmq-titan-brochure-br047004en-en-us.pdf
CATALOGS	eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf eaton-operating-surface-mounting-m22-accessory-dimensions-002.eps eaton-operating-surface-mounting-m22-accessory-3d-drawing.eps eaton-operating-button-symbol-007.eps eaton-general-totally-insulated-t0-main-switch-symbol.eps
DRAWINGS	
ECAD MODEL	ETN.216539.edz
FLYERS	eaton-rmq-titan-selection-aid-brochure-fl047002-en-us.pdf
INSTALLATION INSTRUCTIONS	IL04716003Z
INSTALLATION VIDEOS	RMQ Flat Design
	DA-CD-aufbauehaeuse_gr_4 DA-CS-aufbauehaeuse_gr_4
MCAD MODEL	eaton-aufbauehaeuse-gr4-3d-model.stp eaton-aufbauehaeuse-gr4-drawing.dwg
MULTIMEDIA	MCI Multicolor Light Indicator M22 with SmartWire-DT MCI MultiColor Light Indicator RMQ compact solution easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
FITTED WITH:	High-grade steel screws
CONNECTION TO SMARTWIRE-DT	No
ENCLOSURE MATERIAL	Plastic
ENCLOSURE TYPE	Surface mounting housing
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
FORCE FOR POSITIVE OPENING - MIN	0 N
NUMBER OF COMMAND POSITIONS	4
NUMBER OF LOCATIONS	4
ENCLOSURE COLOR	Gray
MATERIAL QUALITY	Other
OPENING DIAMETER	22.5 mm
RAL-NUMBER	7035
DEGREE OF PROTECTION	NEMA 3R IP67/IP69K
KNOCKOUTS	2 x M20/25 (cable entry knockout at the side, 1 x each side) 2 x M20 (cable entry knockouts at the top) 2 x M20 (cable entry knockouts at the rear)

	RMQ small E-Stop emergency-stop button
PEP ECO-PASSPORT	eaton-pushbutton-control-stations-pep-eato-00299-v0101-en.pdf
SALES NOTES	eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf eaton-control circuit-devices rmq-titan-fl144090en-en-us.pdf eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.