

# Specifications



## Eaton 262704

Eaton Moeller series xPole - PL7 MCB.  
Miniature circuit breaker (MCB), 16 A, 1p,  
characteristic: C

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller series xPole - PL7 MCB
<b>CATALOG NUMBER</b>	262704
<b>MODEL CODE</b>	PL7-C16/1
<b>EAN</b>	4015082627041
<b>PRODUCT LENGTH/DEPTH</b>	71 mm
<b>PRODUCT HEIGHT</b>	82 mm
<b>PRODUCT WIDTH</b>	17.6 mm
<b>PRODUCT WEIGHT</b>	0.12 kg
<b>COMPLIANCES</b>	RoHS conform
<b>GLOBAL CATALOG</b>	262704



Powering Business Worldwide

## Product specifications

<b>USED WITH</b>	Miniature circuit breaker PL7
<b>AMPERAGE RATING</b>	16 A
<b>FEATURES</b>	Additional equipment possible
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF</b>	Does not apply, since the

## Resources

	<a href="#">eaton-xpole-pl7-mcb-catalog-ca019068en-en-us.pdf</a>
CATALOGS	<a href="#">eaton-xpole-protective-devices-catalog-ca019014en-en-us.pdf</a> <a href="#">eaton-xpole-accessories-ca019015en-en-us.pdf</a>
CHARACTERISTIC CURVE	<a href="#">eaton-xpole-mmc4-6-m-mcb-characteristic-curve-002.jpg</a>
DECLARATIONS OF CONFORMITY	<a href="#">eaton-mcb-declaration-of-conformity-eu250401en.pdf</a>
DRAWINGS	<a href="#">eaton-xpole-mmc4-6-m-mcb-dimensions.jpg</a> <a href="#">eaton-xpole-mmc4-6-m-mcb-3d-drawing-007.jpg</a>
INSTALLATION INSTRUCTIONS	<a href="#">eaton-rccb-rcbo-g9-il019140zu.pdf</a>
MCAD MODEL	<a href="#">pls_1p.dwg</a> <a href="#">eaton-non-selective-universal-mcb-mcad-drawings-faz-pls-1p.dwg</a> <a href="#">pls_1p.stp</a>
PEP ECO-PASSPORT	<a href="#">EATO-00046-V01.01-EN</a>
WIRING DIAGRAMS	<a href="#">eaton-xpole-mmc4-6-m-mcb-wiring-diagram-002.jpg</a>

<b>PROTECTION OF ASSEMBLIES</b>	entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>POLLUTION DEGREE</b>	2
<b>DEGREE OF PROTECTION</b>	IP20
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT</b>	2.2 W
<b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b>	4 kV
<b>TRIPPING CHARACTERISTIC</b>	C
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	75 °C
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>BUILT-IN DEPTH</b>	70.5 mm
<b>CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MAX</b>	25 mm <sup>2</sup>
<b>CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MIN</b>	1 mm <sup>2</sup>
<b>CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MAX</b>	25 mm <sup>2</sup>
<b>CONNECTABLE</b>	1 mm <sup>2</sup>

<b>CONDUCTOR CROSS SECTION (SOLID-CORE) - MIN</b>	
<b>CURRENT LIMITING CLASS</b>	3
<b>FREQUENCY RATING - MAX</b>	60 Hz
<b>FREQUENCY RATING - MIN</b>	50 Hz
<b>HEAT DISSIPATION CAPACITY</b>	0 W
<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT</b>	0 W
<b>WIDTH IN NUMBER OF MODULAR SPACINGS</b>	1
<b>VOLTAGE TYPE</b>	AC
<b>OVERVOLTAGE CATEGORY</b>	III
<b>NUMBER OF POLES</b>	Single-pole
<b>RELEASE CHARACTERISTIC</b>	C
<b>TYPE</b>	<ul style="list-style-type: none"> <li>• Miniature circuit breaker</li> <li>• PL7</li> </ul>
<b>SPECIAL FEATURES</b>	Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity
<b>APPLICATION</b>	<ul style="list-style-type: none"> <li>• Switchgear for residential and commercial applications</li> <li>• xPole - Switchgear for residential and commercial applications</li> </ul>
<b>NUMBER OF POLES (PROTECTED)</b>	1
<b>NUMBER OF POLES (TOTAL)</b>	1
<b>RATED INSULATION VOLTAGE (UI)</b>	440 V
<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	16 A
<b>RATED OPERATIONAL VOLTAGE (UE) - MAX</b>	230 V
<b>RATED SHORT-CIRCUIT</b>	10 kA

---

**BREAKING CAPACITY  
(IEC/EN 60898-1) - ICN AT  
230 V**

---

**RATED SHORT-CIRCUIT  
BREAKING CAPACITY  
(IEC/EN 60898-1)- ICN AT  
400 V** 10 kA

---

**RATED SHORT-CIRCUIT  
BREAKING CAPACITY (IEC  
60947-2)- ICU AT 230 V** 0 kA

---

**RATED SHORT-CIRCUIT  
BREAKING CAPACITY (IEC  
60947-2)- ICU AT 400 V** 0 kA

---

**RATED SWITCHING  
CAPACITY (IEC/EN 60898-  
1)** 10 kA

---

**STATIC HEAT  
DISSIPATION, NON-  
CURRENT-DEPENDENT** 0 W

---

**POWER LOSS** 2.3 W

---

---

**PROJECT NAME:**

---

**PROJECT NUMBER:**

---

**PREPARED BY:**

---

**DATE:**

---



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.