

Specifications



Eaton C14M10

Eaton Bussmann series low voltage 14 x 51 mm cylindrical/ferrule fuse, rated at 690 Volts AC, 10 Amps, 80 kA Breaking capacity, class aM, without indicator, compatible with a CH14 Modular fuse holder

General specifications

PRODUCT NAME	Eaton Bussmann series low voltage cylindrical fuse
CATALOG NUMBER	C14M10
MODEL CODE	CYLINDRICAL FUSE 14 x 51 10A AM 690V AC
UPC	051712754675
EAN	5027590494342
PRODUCT LENGTH/DEPTH	51 mm
PRODUCT HEIGHT	14.3 mm
PRODUCT WIDTH	14.3 mm
PRODUCT WEIGHT	20.5 g
COMPLIANCES	GoST-R RoHS Compliant CE Marked
CERTIFICATIONS	IEC 60269
GLOBAL CATALOG	C14M10



Powering Business Worldwide

Product specifications

AMPERAGE RATING	10 A
FUSE SIZE	14 x 51 mm
CURRENT TYPE	AC
BREAKING CAPACITY	80 kA
FREQUENCY RATING - MAX	62 Hz
FREQUENCY RATING - MIN	45 Hz
RATED VOLTAGE AC	690 V
CLASS	Class aM
FUSE TYPE	C14M
UTILIZATION CATEGORY	aM (switchgear protection)
FUSE INDICATOR	Other
WATT LOSSES	0.53 W
CONNECTION	Ferrule end x ferrule end
CONSTRUCTION SIZE	14 mm x 51 mm
FUSE SHAPE	Cylindrical
VOLTAGE TYPE	AC
SUITABLE FOR	CH14 Modular fuse holder
MATERIAL	Ceramic
MOUNTING METHOD	14 x 51 mm CH Modular fuse holder
PACKAGING TYPE	Standard
RELEASE CHARACTERISTIC	Other
QUANTITY	10
VOLTAGE RATING	690 V
TYPE	fuse

APPLICATION

- motor protection
- for industrial applications

Resources

	eaton-bussmann-series-low-voltage-fuses-catalog-ca134002en-en-us.pdf
CATALOGS	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf Bussmann series complete full line catalog no. 1007
DECLARATIONS OF CONFORMITY	eaton-low-voltage-cylindrical-fuse-declaration-of-conformity-eu250463en.pdf eaton-low-voltage-cylindrical-fuse-declaration-of-conformity-uk250946en.pdf
TECHNICAL DATA SHEETS	720115 Cylindrical fuses

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

