

ECM4PO



Specificatii

Cod ETI	001100143
Descriere	ECM4PO
Denumire clasă	Cutie distribu ie
Curent nominal (A)	63
Tensiunea nominală(V)	400
Tip montaj	Culoare aplicată
Grad de protec ie IP	IP40
Clasa de protec ie	II
Numarul de module (total / pe rand)	4 / 4
Dimensiune (numarul de randuri)	1
Usa (material, culoare)	Plastic, white
Parte inferioara cutie (material, culoare)	Plastic, alb
Numarul de terminale PE/N (conexiuni)	4 / 4
Test pentru fire (°C)	650

[Pagina de produse online](#) 

Alta documentatie



[Catalog caracteristici tehnice](#)

[Model 3D](#)

[Manual de instructiuni](#)

[Declaratie CE](#)

[Eplan mușchi](#)

ETIM clasificare internationala

Clasificare	EC000214
Denumire clasă	Small distribution board
Number of rows	1
Width in number of modular spacings	4
Type of covering	Door
Cover model	Closed
Transparent cover/door	
Housing material	Plastic
Height	232mm
Width	139mm
Depth	99mm
Built-in depth	68mm
DIN-rail	1
With mounting plate	
Extension possible	
EMC-version	1
Colour	White
RAL-number	9003
Degree of protection (IP)	IP40

Desen cotat

Flush mounted distribution board

type	Dimensions							Max. allowed power losses when Max. number of devices are installed Pde	Static load
	A	B	C	D	E	F	G		
ECM4PT/ECM4PO	232 mm	139 mm	99 mm	-	123 mm	216 mm	69 mm	>10 W	520 g
ECM8PT/ECM8PO	232 mm	211 mm	99 mm	-	201 mm	212 mm	68 mm	>16 W	1040 g
ECM12PT/ECM12PO	232 mm	283 mm	106 mm	-	273 mm	212 mm	68 mm	>25 W	1560 g
ECM18PT/ECM18PO	232 mm	392 mm	106 mm	-	382 mm	212 mm	68 mm	>25 W	2340 g
ECM24PT/ECM24PO	357 mm	283 mm	106 mm	125 mm	273 mm	336 mm	68 mm	>30 W	1560 g
ECM36PT/ECM36PO	482 mm	283 mm	106 mm	125 mm	273 mm	462 mm	68 mm	>30 W	1560 g
ECM48PT/ECM48PO	676 mm	283 mm	106 mm	125 mm	273 mm	656 mm	68 mm	>30 W	1560 g
ECM2x18PT/ECM2x18PO	357 mm	392 mm	106 mm	125 mm	382 mm	336 mm	68 mm	>30 W	2340 g
ECM3x18PT/ECM3x18PO	522 mm	392 mm	106 mm	125 mm	382 mm	502 mm	68 mm	>35 W	2340 g

