

# ECT48MEDIAPO



## Specificatii

|  |                   |
|--|-------------------|
| Cod ETI                                    | 001100214         |
| Descriere                                  | ECT48MEDIAPO      |
| Denumire clasă                             | Cutie distribu ie |
| Curent nominal (A)                         | 63                |
| Tensiunea nominală(V)                      | 400               |
| Tip montaj                                 | Suprafa ă montată |
| Grad de protec ie IP                       | IP40              |
| Clasa de protec ie                         | II                |
| Numarul de module (total / pe rand)        | 12                |
| Dimensiune (numarul de randuri)            | 4                 |
| Usa (material, culoare)                    | Plastic, white    |
| Parte inferioara cutie (material, culoare) | Plastic, alb      |
| Test pentru fire (°C)                      | 650               |

[Pagina de produse online](#) 

## Alta documentatie



[Catalog caracteristici tehnice](#)

[Model 3D](#)

[Manual de instructiuni](#)

[Declaratie CE](#)

[Eplan mușchi](#)

## ETIM clasificare internationala

|                                     |                           |
|-------------------------------------|---------------------------|
| Clasificare                         | EC000214                  |
| Denumire clasă                      | Small distribution board  |
| Mounting method                     | Surface mounted (plaster) |
| Number of rows                      | 4                         |
| Width in number of modular spacings | 12                        |
| Type of covering                    | Door                      |
| Cover model                         | Closed                    |
| Housing material                    | Plastic                   |
| Colour                              | White                     |
| Degree of protection (IP)           | IP40                      |
| Type of closure                     | Other                     |

## Desen cotat

| Surface mounted distribution board |              |        |        |        |        |       |             |
|------------------------------------|--------------|--------|--------|--------|--------|-------|-------------|
| type                               | Dimensions** |        |        |        |        | Pde*  | Static load |
|                                    | A            | B      | C      | D      | E      |       |             |
| ECT4PT/ECT4PO                      | 235 mm       | 143 mm | 98 mm  | 127 mm | 46 mm  | >10 W | 520 g       |
| ECT8PT/ECT8PO                      | 236 mm       | 215 mm | 102mm  | 107 mm | 120 mm | >16 W | 1040 g      |
| ECT12PT/ECT12PO                    | 236 mm       | 287 mm | 112 mm | 107 mm | 180 mm | >25 W | 1560 g      |
| ECT18PT/ECT18PT                    | 236 mm       | 396 mm | 112 mm | 107 mm | 289 mm | >25 W | 2340 g      |
| ECT24PT/ECT24PO                    | 361 mm       | 287 mm | 112 mm | 232 mm | 180 mm | >30 W | 1560 g      |
| ECT36PT/ECT36PO                    | 485 mm       | 287 mm | 112 mm | 357 mm | 180 mm | >30 W | 1560 g      |
| ECT48PT/ECT48PO                    | 652 mm       | 287 mm | 112 mm | 482 mm | 180 mm | >35 W | 1560 g      |
| ECT2x18PT/ECT2x18PO                | 361 mm       | 396mm  | 112 mm | 232 mm | 289 mm | >30 W | 2340 g      |
| ECT3x18PT/ECT3x18PO                | 526 mm       | 396mm  | 112 mm | 357 mm | 289 mm | >35 W | 2340 g      |
| ECT4x18PT/ECT4x18PO                | 651 mm       | 396mm  | 112 mm | 357 mm | 289 mm | >40 W | 2340 g      |

\* Max. allowed power losses when Max. number of devices are installed

\*\*Sizes are also valid for IT distribution boards DIDO-E MEDIA: ECT...MEDIA

