

ECM12PT



Specificatii

| | |
|--|----------------------|
| Cod ETI | 001101011 |
| Descriere | ECM12PT |
| Denumire clasă | Cutie distribu ie |
| Curent nominal (A) | 63 |
| Tensiunea nominală(V) | 400 |
| Tip montaj | Culoare aplicată |
| Grad de protec ie IP | IP40 |
| Clasa de protec ie | II |
| Numarul de module (total / pe rand) | 12 / 12 |
| Dimensiune (numarul de randuri) | 1 |
| Usa (material, culoare) | Plastic, transparent |
| Parte inferioara cutie (material, culoare) | Plastic, alb |
| Numarul de terminale PE/N (conexiuni) | 10 / 10 |
| Test pentru fire (°C) | 650 |

[Pagina de produse online](#) 

Alta documentatie



[Catalog caracteristici tehnice](#)

[Model 3D](#)

[Manual de instructiuni](#)

[Declaratie CE](#)

[Eplan mușchi](#)

ETIM clasificare internationala

| | |
|-------------------------------------|--------------------------|
| Clasificare | EC000214 |
| Denumire clasă | Small distribution board |
| Mounting method | Flush-mounted (plaster) |
| Number of rows | 1 |
| Width in number of modular spacings | 12 |
| Housing material | Plastic |
| Height | 232mm |
| Width | 283mm |
| Depth | 106mm |
| Built-in depth | 68mm |
| DIN-rail | 1 |
| EMC-version | 1 |
| Colour | White |
| Degree of protection (IP) | IP40 |

Desen cotat

Flush mounted distribution board

| type | Dimensions | | | | | | | Max. allowed power losses when Max. number of devices are installed Pde | Static load |
|---------------------|------------|--------|--------|--------|--------|--------|-------|--|-------------|
| | A | B | C | D | E | F | G | | |
| ECM4PT/ECM4PO | 232 mm | 139 mm | 99 mm | - | 123 mm | 216 mm | 69 mm | >10 W | 520 g |
| ECM8PT/ECM8PO | 232 mm | 211 mm | 99 mm | - | 201 mm | 212 mm | 68 mm | >16 W | 1040 g |
| ECM12PT/ECM12PO | 232 mm | 283 mm | 106 mm | - | 273 mm | 212 mm | 68 mm | >25 W | 1560 g |
| ECM18PT/ECM18PO | 232 mm | 392 mm | 106 mm | - | 382 mm | 212 mm | 68 mm | >25 W | 2340 g |
| ECM24PT/ECM24PO | 357 mm | 283 mm | 106 mm | 125 mm | 273 mm | 336 mm | 68 mm | >30 W | 1560 g |
| ECM36PT/ECM36PO | 482 mm | 283 mm | 106 mm | 125 mm | 273 mm | 462 mm | 68 mm | >30 W | 1560 g |
| ECM48PT/ECM48PO | 676 mm | 283 mm | 106 mm | 125 mm | 273 mm | 656 mm | 68 mm | >30 W | 1560 g |
| ECM2x18PT/ECM2x18PO | 357 mm | 392 mm | 106 mm | 125 mm | 382 mm | 336 mm | 68 mm | >30 W | 2340 g |
| ECM3x18PT/ECM3x18PO | 522 mm | 392 mm | 106 mm | 125 mm | 382 mm | 502 mm | 68 mm | >35 W | 2340 g |

