

ECG14PO



Specificatii

| | |
|--|-------------------|
| Cod ETI | 001101183 |
| Descriere | ECG14PO |
| Denumire clasă | Cutie distribu ie |
| Curent nominal (A) | 63 |
| Tensiunea nominală(V) | 400 |
| Tip montaj | Culoare aplicată |
| Grad de protec ie IP | IP40 |
| Clasa de protec ie | II |
| Numarul de module (total / pe rand) | 14 / 14 |
| Dimensiune (numarul de randuri) | 1 |
| Usa (material, culoare) | Plastic, white |
| Parte inferioara cutie (material, culoare) | Plastic, alb |
| Test pentru fire (°C) | 650 |

[Pagina de produse online](#) 

Alta documentatie



[Catalog caracteristici tehnice](#)

[Model 3D](#)

[Manual de instructiuni](#)

[Declaratie CE](#)

[Eplan mușchi](#)

ETIM clasificare internațională

| | |
|-------------------------------------|--------------------------|
| Clasificare | EC000214 |
| Denumire clasă | Small distribution board |
| Mounting method | Flush-mounted (plaster) |
| Number of rows | 1 |
| Width in number of modular spacings | 14 |
| Housing material | Plastic |
| Height | 317mm |
| Width | 346mm |
| Depth | 87mm |
| Built-in depth | 88mm |
| DIN-rail | |
| With mounting plate | 1 |
| EMC-version | 1 |
| Colour | White |
| Degree of protection (IP) | IP40 |

Desen cotat

| Flush mounted distribution board | | | | | | |
|----------------------------------|------------|--------|-------|--------|--------|--|
| type | Dimensions | | | | | Max. allowed power losses when Max. number of devices are installed Pde |
| | A | B | C | H | W | |
| ECG14 | 274 mm | 306 mm | 87 mm | 317 mm | 346 mm | 31 W |
| ECG28 | 399 mm | 306 mm | 87 mm | 442 mm | 346 mm | 40 W |
| ECG42 | 549 mm | 306 mm | 87 mm | 592 mm | 346 mm | 50 W |
| ECG56 | 673 mm | 306 mm | 87 mm | 717 mm | 346 mm | 60 W |
| ECG70 | 799 mm | 306 mm | 87 mm | 842 mm | 346 mm | 70 W |

