

SL2 3P SP.300



Specificatii

Cod ETI	001692000
Descriere	SL2 3P SP.300
Denumire clasă	Siguranță verticală
Curent nominal (A)	400
Mărime	NH2
Număr de poli	3
Grup de produse	Separatoare verticale pentru siguranțe fuzibile JT
Tensiune nominală AC (V)	690
Grad de protecție IP	IP30
Categorie de utilizare	AC-23B
Conectare	SP.300
Montare	șurub

[Pagina de produse online](#) 

Alta documentatie



[Catalog caracteristici tehnice](#)

[CertIFICATE](#)

[Model 3D](#)

[Manual de instructiuni](#)

[Declaratie CE](#)

[Eplan mușchi](#)

ETIM clasificare internațională

Clasificare	EC001040
Denumire clasă	Fuse switch disconnector
Version as main switch	
Version as safety switch	
Max. rated operation voltage Ue AC	690V
Rated permanent current Iu	400A
Rated operation power at AC-23, 400 V	277kW
Conditioned rated short-circuit current Iq	120kA
Suitable for fuses	NH1
Number of poles	3
With error protection	
Type of electrical connection of main circuit	Frame clamp
Cable entry	Other
Equipped with connectors	
Suitable for floor mounting	
Suitable for front mounting	
Suitable for busbar mounting	1
Type of control element	Other
Position control element	Front side
Motor drive optional	
Motor drive integrated	
Version as emergency stop installation	
Degree of protection (IP), front side	IP30

Desen cotat

