

# SL00 1P M8



## Specificatii

Cod ETI	001692010
Descriere	SL00 1P M8
Denumire clasă	Siguranță verticală
Curent nominal (A)	160
Mărime	NH00
Număr de poli	3
Grup de produse	Separatoare verticale pentru siguranțe fuzibile JT
Tensiune nominală AC (V)	690
Grad de protecție IP	IP30
Categorie de utilizare	AC-23B
Conectare	M8
Montare	șurub

[Pagina de produse online](#) 

## Alta documentatie



[Catalog caracteristici tehnice](#)

[Model 3D](#)

[Manual de instructiuni](#)

[Declaratie CE](#)

[Eplan mușchi](#)

## ETIM clasificare internațională

Clasificare	EC001040
Denumire clasă	Fuse switch disconnector
Version as main switch	
Version as safety switch	
Max. rated operation voltage Ue AC	690V
Rated permanent current Iu	160A
Rated operation power at AC-23, 400 V	110kW
Conditioned rated short-circuit current Iq	120kA
Suitable for fuses	NH000, NH00
Number of poles	3
With error protection	
Type of electrical connection of main circuit	Screw connection
Cable entry	Other
Equipped with connectors	
Suitable for floor mounting	
Suitable for front mounting	
Suitable for busbar mounting	1
Type of control element	Other
Position control element	Front side
Motor drive optional	
Motor drive integrated	
Version as emergency stop installation	
Degree of protection (IP), front side	IP30

