

# ETIMAT P10 3p+N B20



## Specificatii

|  |                        |
|--|------------------------|
| Cod ETI                                    | 001901411              |
| Descriere                                  | ETIMAT P10 3p+N B20    |
| Denumire clasă                             | Înterupător de circuit |
| Funcție                                    | MCB                    |
| Capacitatea de rupere (kA)                 | 10                     |
| Caracteristică de întrerupere              | B                      |
| Curent nominal (A)                         | 20                     |
| Tensiunea nominală(V)                      | 415                    |
| Număr de poli                              | 3+N                    |
| Frecvență nominală (Hz)                    | 50/60                  |
| Standarde                                  | EN/IEC 60898           |
| Secțiune transversală nominală             | 1-25                   |
| Tipul voltajului                           | AC                     |
| Tensiunea nominală de rezistență Uimp (kV) | 6kV                    |

[Pagina de produse online](#) 

## Alta documentatie



[Catalog caracteristici tehnice](#)

[Model 3D](#)

[Manual de instructiuni](#)

[Declaratie CE](#)

[Eplan mușchi](#)

## ETIM clasificare internațională

|  |                                 |
|--|---------------------------------|
| Clasificare  | EC000042                        |
| Denumire clasă   | Miniature circuit breaker (MCB) |
| Release characteristic   | B                               |
| Number of poles (total)  | 4                               |
| Number of protected poles  | 3                               |
| Rated current  | 20A                             |
| Rated voltage  | 415V                            |
| Rated insulation voltage $U_i$   | 500V                            |
| Rated impulse withstand voltage $U_{imp}$  | 6kV                             |
| Rated short-circuit breaking capacity $I_{cn}$ according to EN 60898 at 230 V    | 10kA                            |
| Rated short-circuit breaking capacity $I_{cn}$ according to EN 60898 at 400 V    | 10kA                            |
| Rated short-circuit breaking capacity $I_{cu}$ according to IEC 60947-2 at 230 V | 10kA                            |
| Rated short-circuit breaking capacity $I_{cu}$ according to IEC 60947-2 at 400 V | 10kA                            |
| Voltage type   | AC                              |
| Frequency  | 50...60Hz                       |
| Current limiting class   | 3                               |
| Suitable for flush-mounted installation  | 1                               |
| Concurrently switching neutral conductor   | 1                               |
| Over voltage category  | 3                               |
| Pollution degree   | 2                               |
| Additional equipment possible  | 1                               |
| Width in number of modular spacings  | 4                               |
| Built-in depth   | 70mm                            |
| Degree of protection (IP)  | IP20                            |
| Ambient temperature during operating   | -40...70°C                      |
| Connectable conductor cross section multi-wired                                  | 1...25mm <sup>2</sup>           |
| Connectable conductor cross section solid-core                                   | 1...25mm <sup>2</sup>           |

# Caracteristicile energiei de topire



# Caracteristici



## Desen cotat



## Simbol/Conexiune

1p



1p+n



2p



3p



3p+n

