

# ETIMAT P10-DC 1p B6



## Specificatii

Cod ETI	001903007
Descriere	ETIMAT P10-DC 1p B6
Denumire clasă	Înterupător de circuit
Funcție	MCB
Capacitatea de rupere (kA)	10
Caracteristică de întrerupere	B
Curent nominal (A)	6
Tensiunea nominală(V)	220
Număr de poli	1
Frecvență nominală (Hz)	1...25
Standarde	60898-2
Secțiune transversală nominală	1...25
Tipul voltajului	DC
Tensiunea nominală de rezistență Uimp (kV)	6

[Pagina de produse online](#)

## Alta documentatie



[Model 3D](#)

[Manual de instructiuni](#)

[Declaratie CE](#)

[Eplan mușchi](#)

## ETIM clasificare internațională

Clasificare	EC000042
Denumire clasă	Miniature circuit breaker (MCB)
Release characteristic	B
Number of poles (total)	1
Number of protected poles	1
Rated current	6A
Rated voltage	220V
Rated insulation voltage $U_i$	500V
Rated impulse withstand voltage $U_{imp}$	6kV
Rated short-circuit breaking capacity $I_{cn}$ according to EN 60898 at 230 V	10kA
Rated short-circuit breaking capacity $I_{cn}$ according to EN 60898 at 400 V	10kA
Rated short-circuit breaking capacity $I_{cu}$ according to IEC 60947-2 at 230 V	10kA
Rated short-circuit breaking capacity $I_{cu}$ according to IEC 60947-2 at 400 V	10kA
Voltage type	DC
Frequency	1...25Hz
Current limiting class	3
Suitable for flush-mounted installation	1
Concurrently switching neutral conductor	1
Over voltage category	3
Pollution degree	2
Additional equipment possible	1
Width in number of modular spacings	1
Built-in depth	70mm
Degree of protection (IP)	IP20
Ambient temperature during operating	-40...70°C
Connectable conductor cross section multi-wired	1...25mm <sup>2</sup>
Connectable conductor cross section solid-core	1...25mm <sup>2</sup>

# Caracteristici



## Desen cotat



## Simbol/Conexiune

