

ETIMAT 10 2p C80



Specificatii

Cod ETI	002133731
Descriere	ETIMAT 10 2p C80
Denumire clasă	Înterupător de circuit
Func ie	MCB
Capacitatea de rupere (kA)	20
Caracteristică de întrerupere	C
Curent nominal (A)	80
Tensiunea nominală(V)	415
Număr de poli	2
Frecven ă nominală (Hz)	50/60
Standarde	IEC/EN 60898-1, IEC 60947-2
Sec iune transversală nominală	2.5 - 50
Tipul voltajului	AC
Tensiunea nominala de rezistenta Uimp (kV)	4

[Pagina de produse online](#)

Alta documentatie



[Catalog caracteristici tehnice](#)

[Model 3D](#)

[Declaratie CE](#)

[Eplan mușchi](#)

ETIM clasificare internațională


Clasificare	EC000042
Denumire clasă	Miniature circuit breaker (MCB)
Release characteristic	C
Number of poles (total)	2
Number of protected poles	2
Rated current	80A
Rated voltage	415V
Rated insulation voltage U_i	440V
Rated impulse withstand voltage U_{imp}	4kV
Rated short-circuit breaking capacity I_{cu} according to IEC 60947-2 at 230 V	20kA
Rated short-circuit breaking capacity I_{cu} according to IEC 60947-2 at 400 V	20kA
Voltage type	Other
Frequency	50...60Hz
Current limiting class	3
Over voltage category	3
Pollution degree	3
Additional equipment possible	1
Width in number of modular spacings	3
Built-in depth	75mm
Degree of protection (IP)	IP20
Ambient temperature during operating	-25...55°C
Connectable conductor cross section multi-wired	2.5...50mm ²
Connectable conductor cross section solid-core	2.5...50mm ²

Desen cotat


•

Simbol/Conexiune


1P




1P+N



2P



3P



3P+N

