

ETIMAT 10 3p C80



Specificatii

| | |
|--|-----------------------------|
| Cod ETI | 002135731 |
| Descriere | ETIMAT 10 3p C80 |
| Denumire clasă | Înterupător de circuit |
| Funcție | MCB |
| Capacitatea de rupere (kA) | 20 |
| Caracteristică de întrerupere | C |
| Curent nominal (A) | 80 |
| Tensiunea nominală(V) | 415 |
| Număr de poli | 3 |
| Frecvență nominală (Hz) | 50/60 |
| Standarde | IEC/EN 60898-1, IEC 60947-2 |
| Secțiune transversală nominală | 2.5 - 50 |
| Tipul voltajului | AC |
| Tensiunea nominala de rezistență Uimp (kV) | 4 |

[Pagina de produse online](#) 

Alta documentatie



[Catalog caracteristici tehnice](#)

[Model 3D](#)

[Declaratie CE](#)

[Eplan mușchi](#)

ETIM clasificare internațională


| | |
|--|---------------------------------|
| Clasificare | EC000042 |
| Denumire clasă | Miniature circuit breaker (MCB) |
| Release characteristic | C |
| Number of poles (total) | 3 |
| Number of protected poles | 3 |
| Rated current | 80A |
| Rated voltage | 415V |
| Rated insulation voltage U_i | 440V |
| Rated impulse withstand voltage U_{imp} | 4kV |
| Rated short-circuit breaking capacity I_{cu} according to IEC 60947-2 at 230 V | 20kA |
| Rated short-circuit breaking capacity I_{cu} according to IEC 60947-2 at 400 V | 20kA |
| Voltage type | Other |
| Frequency | 50...60Hz |
| Current limiting class | 3 |
| Over voltage category | 3 |
| Pollution degree | 3 |
| Additional equipment possible | 1 |
| Width in number of modular spacings | 4,5 |
| Built-in depth | 75mm |
| Degree of protection (IP) | IP20 |
| Ambient temperature during operating | -25...55°C |
| Connectable conductor cross section multi-wired | 2.5...50mm ² |
| Connectable conductor cross section solid-core | 2.5...50mm ² |

Desen cotat


•

Simbol/Conexiune

1P




1P+N



2P



3P



3P+N

