

ETIMAT 10 4p C125



Specificatii

Cod ETI	002137733
Descriere	ETIMAT 10 4p C125
Denumire clasă	Înterupător de circuit
Func ie	MCB
Capacitatea de rupere (kA)	15
Caracteristică de întrerupere	C
Curent nominal (A)	125
Tensiunea nominală(V)	415
Număr de poli	4
Frecven ă nominală (Hz)	50/60
Standarde	IEC/EN 60947-2
Sec iune transversală nominală	2.5 - 50
Tipul voltajului	AC
Tensiunea nominala de rezistenta Uimp (kV)	4

[Pagina de produse online](#) 

Alta documentatie



[Catalog caracteristici tehnice](#)

[Model 3D](#)

[Declaratie CE](#)

[Eplan mușchi](#)

ETIM clasificare internațională

Clasificare	EC000042
Denumire clasă	Miniature circuit breaker (MCB)
Release characteristic	C
Number of poles (total)	4
Number of protected poles	4
Rated current	125A
Rated voltage	415V
Rated insulation voltage U_i	440V
Rated impulse withstand voltage U_{imp}	4kV
Rated short-circuit breaking capacity I_{cu} according to IEC 60947-2 at 230 V	15kA
Rated short-circuit breaking capacity I_{cu} according to IEC 60947-2 at 400 V	15kA
Voltage type	Other
Frequency	50...60Hz
Current limiting class	3
Over voltage category	3
Pollution degree	3
Additional equipment possible	1
Width in number of modular spacings	6
Built-in depth	75mm
Degree of protection (IP)	IP20
Ambient temperature during operating	-25...55°C
Connectable conductor cross section multi-wired	2.5...50mm ²
Connectable conductor cross section solid-core	2.5...50mm ²