

## KZS-2M AC B25/0.3



### Specificatii

|                               |                   |
|-------------------------------|-------------------|
| Cod ETI                       | 002173306         |
| Descriere                     | KZS-2M AC B25/0.3 |
| Denumire clasă                | Diferențial RCBO  |
| Capacitatea de rupere (kA)    | 10                |
| Caracteristică de întrerupere | B                 |
| Curent nominal (A)            | 20                |
| Tip                           | AC                |
| Curent de defect nominal (A)  | 0.3               |
| Tip curent                    | AC                |
| Tensiunea nominală(V)         | 240               |
| Număr de poli                 | 1+N               |
| Frecvență nominală (Hz)       | 50/60 Hz          |
| Standarde                     | IEC/EN 61009      |
| Seciune transversală nominală | 1-25              |

[Pagina de produse online](#)

### Alta documentatie



[Catalog caracteristici tehnice](#)

[Model 3D](#)

[Manual de instructiuni](#)

[Declaratie CE](#)

[Eplan mușchi](#)

## ETIM clasificare internațională

|   |                               |
|---|-------------------------------|
| Clasificare   | EC000905                      |
| Denumire clasă  | Earth leakage circuit breaker |
| Number of poles (total)                                     | 2                             |
| Number of protected poles                                   | 1                             |
| Rated voltage   | 230V                          |
| Rated insulation voltage $U_i$                              | 500V                          |
| Rated current   | 20A                           |
| Rated fault current   | 0,3A                          |
| Leakage current type  | AC                            |
| Current limiting class                                      | 3                             |
| Rated short-circuit breaking capacity according to EN 61009 | 10kA                          |
| Voltage type  | AC                            |
| Frequency   | 50/60 Hz                      |
| Release characteristic                                      | B                             |
| Concurrently switching neutral conductor                    | 1                             |
| Width in number of modular spacings                         | 2                             |
| Built-in depth  | 69mm                          |
| Degree of protection (IP)                                   | IP20                          |
| Connectable conductor cross section solid-core              | 1...25mm <sup>2</sup>         |
| Connectable conductor cross section multi-wired             | 1...25mm <sup>2</sup>         |

## Desen cotat



## Simbol/Conexiune

