

KZS-2M A C20/0.3



Specificatii

| | |
|-------------------------------|------------------|
| Cod ETI | 002173425 |
| Descriere | KZS-2M A C20/0.3 |
| Denumire clasă | Diferențial RCBO |
| Capacitatea de rupere (kA) | 10 |
| Caracteristică de întrerupere | C |
| Curent nominal (A) | 20 |
| Tip | A |
| Curent de defect nominal (A) | 0.3 |
| Tip curent | A |
| Tensiunea nominală(V) | 240 |
| Număr de poli | 1+N |
| Frecvență nominală (Hz) | 50/60 Hz |
| Standarde | IEC/EN 61009 |
| Seciune transversală nominală | 1-25 |

[Pagina de produse online](#)

Alta documentatie



[Catalog caracteristici tehnice](#)

[Model 3D](#)

[Manual de instructiuni](#)

[Declaratie CE](#)

[Eplan mușchi](#)

ETIM clasificare internațională

| | |
|-------------------------------------------------------------|-------------------------------|
| Clasificare | EC000905 |
| Denumire clasă | Earth leakage circuit breaker |
| Number of poles (total) | 2 |
| Number of protected poles | 1 |
| Rated voltage | 230V |
| Rated insulation voltage U_i | 500V |
| Rated current | 20A |
| Rated fault current | 0,3A |
| Leakage current type | A |
| Current limiting class | 3 |
| Rated short-circuit breaking capacity according to EN 61009 | 10kA |
| Voltage type | AC |
| Frequency | 50 Hz |
| Release characteristic | C |
| Concurrently switching neutral conductor | 1 |
| Width in number of modular spacings | 2 |
| Built-in depth | 69mm |
| Degree of protection (IP) | IP20 |
| Connectable conductor cross section solid-core | 1...25mm ² |
| Connectable conductor cross section multi-wired | 1...25mm ² |

Desen cotat



