

# KZS-4M 3p+N A B10/0.1



## Specificatii

|                                |                       |
|--------------------------------|-----------------------|
| Cod ETI                        | 002174402             |
| Descriere                      | KZS-4M 3p+N A B10/0.1 |
| Denumire clasă                 | Diferențial RCBO      |
| Capacitatea de rupere (kA)     | 6                     |
| Caracteristică de întrerupere  | B                     |
| Curent nominal (A)             | 10                    |
| Tip                            | A                     |
| Curent de defect nominal (A)   | 0.1                   |
| Tip curent                     | A                     |
| Tensiunea nominală(V)          | 415                   |
| Număr de poli                  | 3+N                   |
| Frecvență nominală (Hz)        | 50/60 Hz              |
| Standarde                      | IEC/EN 61009          |
| Secțiune transversală nominală | 1-25                  |

[Pagina de produse online](#)

## Alta documentatie



[Catalog caracteristici tehnice](#)

[CertIFICATE](#)

[Model 3D](#)

[Manual de instructiuni](#)

[Declaratie CE](#)

[Eplan mușchi](#)

## ETIM clasificare internațională

|   |                               |
|---|-------------------------------|
| Clasificare   | EC000905                      |
| Denumire clasă  | Earth leakage circuit breaker |
| Number of poles (total)                                     | 4                             |
| Number of protected poles                                   | 3                             |
| Rated voltage   | 400V                          |
| Rated current   | 10A                           |
| Rated fault current   | 0,1A                          |
| Leakage current type  | A                             |
| Current limiting class                                      | 3                             |
| Rated short-circuit breaking capacity according to EN 61009 | 6kA                           |
| Frequency   | 50/60 Hz                      |
| Release characteristic                                      | B                             |
| Concurrently switching neutral conductor                    | 1                             |
| Width in number of modular spacings                         | 4                             |
| Built-in depth  | 69mm                          |
| Degree of protection (IP)                                   | IP20                          |
| Connectable conductor cross section solid-core              | 1...25mm <sup>2</sup>         |
| Connectable conductor cross section multi-wired             | 1...25mm <sup>2</sup>         |

## Desen cotat



## Simbol/Conexiune

