

R 25-13 24V



Specificatii

| | |
|---------------------------------|-------------------|
| Cod ETI | 002462331 |
| Descriere | R 25-13 24V |
| Denumire clasă | Contactor modular |
| Func ie | Contactor modular |
| Tip | AC |
| Mărime | 4p, 2-modules |
| Număr de contacte NC | 3 |
| Frecven ă nominală (Hz) | 50/60 |
| Număr contacte NO | 1 |
| Curent nominal la AC-1/AC-7 (A) | 25 |
| Tensiunea nominala (V AC) | 440V |
| Tensiunea de control Uc (V AC) | 24V |

Pagina de produse online [🔗](#)

Alta documentatie



Model 3D

Declaratie CE

Eplan mușchi

Catalog caracteristici tehnice

ETIM clasificare internationala

| | |
|---|---|
| Clasificare | EC001653 |
| Denumire clasă | Installation contactor for distribution board |
| Rated operating voltage | 230...400V |
| Rated operation current | 25A |
| Rated excitation voltage | 24...24V |
| Voltage type (operating voltage) | AC |
| Voltage type (excitation voltage) | AC |
| Number of contacts as normally open contact | 1 |
| Number of contacts as normally closed contact | 3 |
| Max. incandescent lamp load | 3000W |
| Max. load fluorescent lamp | 1190VA |
| Max. load fluorescent lamp (Duo circuit) | 2552VA |
| Max. load fluorescent lamp (parallel compensated) | 1360VA |
| Slider for hand switch | |
| Number of modular spacings | 2 |
| Built-in depth | 60mm |
| Additional equipment possible | 1 |
| Degree of protection (IP) | IP20 |

Desen cotat

R25

165,150

