

R 40-04 24V



Specificatii

Cod ETI	002463441
Descriere	R 40-04 24V
Denumire clasă	Contactor modular
Func ie	Contactor modular
Tip	AC
Mărime	4p, 3-modules
Număr de contacte NC	4
Frecven ă nominală (Hz)	50/60
Număr contacte NO	0
Curent nominal la AC-1/AC-7 (A)	40
Tensiunea nominala (V AC)	440V
Tensiunea de control Uc (V AC)	24V

Pagina de produse online [🔗](#)

Alta documentatie



Model 3D

Declaratie CE

Eplan mușchi

Catalog caracteristici tehnice

ETIM clasificare internationala

Clasificare	EC001653
Denumire clasă	Installation contactor for distribution board
Rated operating voltage	230...400V
Rated operation current	40A
Rated excitation voltage	24...24V
Voltage type (operating voltage)	AC
Voltage type (excitation voltage)	AC
Number of contacts as normally closed contact	4
Max. incandescent lamp load	6000W
Max. load fluorescent lamp	2975VA
Max. load fluorescent lamp (Duo circuit)	5280VA
Max. load fluorescent lamp (parallel compensated)	2805VA
Slider for hand switch	
Number of modular spacings	3
Built-in depth	60mm
Additional equipment possible	1
Degree of protection (IP)	IP20

Desen cotat

R40,R63

Limits 190,120

