

HRN-32/2



Specificatii

Cod ETI	002471452
Descriere	HRN-32/2
Denumire clasă	Releu control
Func ie	Relee monitorizare și control
Curent nominal (A)	16
AC Tensiunea bobinei Uc (V)	48...276
Număr contacte CO	2
DC tensiunea nominală a bobinei Uc (V)	48...276
Tipul voltajului	AC/DC
Tensiunea de alimentare (V)	48-276
Numarul de contacte	1
Tipul de control	Umin and Umax
Capacitatea maxima de incarcare AC1 (VA)	4000

Pagina de produse online [🔗](#)

Alta documentatie



Catalog caracteristici tehnice

Model 3D

Manual de instructiuni




Declaratie CE

Eplan mușchi


ETIM clasificare internationala

Clasificare	EC001438
Denumire clasă	Voltage monitoring relay
Type of electric connection	Screw connection
Single-phase under voltage possible	1
Single-phase over voltage possible	1
Voltage measuring range 1	48...276V
Type of voltage measuring range	AC/DC
Rated control supply voltage AC 50 Hz	48...276V
Voltage type for actuating	AC
Min. adjustable delay-on energization time	0,5s
Max. permitted delay-on energization time	10s
Min. adjustable off-delay time	0,5s
Max. permitted off-delay time	10s
Number of contacts as change-over contact	1
Width	18mm
Height	90mm
Depth	65mm


Simbol/Conexiune



HRN-33



HRN-34



HRN-35

