

# MPE25-0,16



## Specificatii

|  |                             |
|--|-----------------------------|
| Cod ETI                                | 004648001                   |
| Descriere                              | MPE25-0,16                  |
| Denumire clasă                         | Înterupător protec ie motor |
| Domeniul de setare al curentului (A)   | 0,1 - 0,16                  |
| Curent scurcircuit I <sub>rm</sub> (A) | 2,08                        |
| Tensiunea maxima de operare (V AC)     | 690                         |

[Pagina de produse online](#)

## Alta documentatie



[Catalog caracteristici tehnice](#)

[Model 3D](#)

[Manual de instructiuni](#)

[Declaratie CE](#)

[Eplan mușchi](#)

## ETIM clasificare internațională

|  |  |
|--|--|
| Clasificare  | EC000074                                 |
| Denumire clasă   | Motor protection circuit-breaker         |
| Overload release current setting                                   | 0.10...0.16A                             |
| Adjustment range undelayed short-circuit release                   | 2...2A                                   |
| Phase failure sensitive  | 1  |
| Switch off technique   | Thermomagnetic                           |
| Rated operating voltage  | 400...690V                               |
| Rated permanent current I <sub>u</sub>                             | 0,16A                                    |
| Type of electrical connection of main circuit                      | Frame clamp                              |
| Device construction  | Built-in device fixed built-in technique |
| With integrated auxiliary switch                                   |  |
| With integrated under voltage release                              |  |
| Number of poles  | 3  |
| Rated short-circuit breaking capacity I <sub>cu</sub> at 400 V, AC | 100kA                                    |
| Degree of protection (IP)  | IP20                                     |

## Desen cotat

