

MPE25-0,25



Specificatii

Cod ETI	004648002
Descriere	MPE25-0,25
Denumire clasă	Înterupător protec ie motor
P (AC3 kW) (kW)	0,06
Domeniul de setare al curentului (A)	0,16 - 0,25
Curent scurcircuit I _{rm} (A)	3,25
Tensiunea maxima de operare (V AC)	690

[Pagina de produse online](#)

Alta documentatie



[Catalog caracteristici tehnice](#)

[Model 3D](#)

[Manual de instructiuni](#)

[Declaratie CE](#)

[Eplan mușchi](#)

ETIM clasificare internationala

Clasificare	EC000074
Denumire clasă	Motor protection circuit-breaker
Overload release current setting	0.16...0.25A
Adjustment range undelayed short-circuit release	3.2...3.2A
Phase failure sensitive	1
Switch off technique	Thermomagnetic
Rated operating voltage	400...690V
Rated permanent current I _u	0,25A
Rated operation power at AC-3, 230 V	0,06kW
Rated operation power at AC-3, 400 V	0,06kW
Type of electrical connection of main circuit	Frame clamp
Device construction	Built-in device fixed built-in technique
With integrated auxiliary switch	
With integrated under voltage release	
Number of poles	3
Rated short-circuit breaking capacity I _{cu} at 400 V, AC	100kA
Degree of protection (IP)	IP20

Desen cotat

