

# MPE25-1,0



## Specificatii

Cod ETI	004648005
Descriere	MPE25-1,0
Denumire clasă	Înterupător protec ie motor
P (AC3 kW) (kW)	0,25
Domeniul de setare al curentului (A)	0,63 - 1,0
Curent scurcircuit I <sub>rm</sub> (A)	13
Tensiunea maxima de operare (V AC)	690

[Pagina de produse online](#)

## Alta documentatie



[Catalog caracteristici tehnice](#)

[Model 3D](#)

[Manual de instructiuni](#)

[Declaratie CE](#)

[Eplan mușchi](#)

## ETIM clasificare internationala

Clasificare	EC000074
Denumire clasă	Motor protection circuit-breaker
Overload release current setting	0.63...1.0A
Adjustment range undelayed short-circuit release	13...13A
Phase failure sensitive	1
Switch off technique	Thermomagnetic
Rated operating voltage	400...690V
Rated permanent current I <sub>u</sub>	1A
Rated operation power at AC-3, 230 V	0,25kW
Rated operation power at AC-3, 400 V	0,25kW
Type of electrical connection of main circuit	Frame clamp
Device construction	Built-in device fixed built-in technique
With integrated auxiliary switch	
With integrated under voltage release	
Number of poles	3
Rated short-circuit breaking capacity I <sub>cu</sub> at 400 V, AC	100kA
Degree of protection (IP)	IP20

## Desen cotat

