

MPE25-1,6



Specificatii

Cod ETI	004648006
Descriere	MPE25-1,6
Denumire clasă	Înterupător protec ie motor
P (AC3 kW) (kW)	0,37
Domeniul de setare al curentului (A)	1,0 - 1,6
Curent scurcircuit I _{rm} (A)	20,8
Tensiunea maxima de operare (V AC)	690

[Pagina de produse online](#) 

Alta documentatie



[Catalog caracteristici tehnice](#)

[Model 3D](#)

[Manual de instructiuni](#)

[Declaratie CE](#)

[Eplan mușchi](#)

ETIM clasificare internationala

Clasificare	EC000074
Denumire clasă	Motor protection circuit-breaker
Overload release current setting	1.0...1.6A
Adjustment range undelayed short-circuit release	20.8...20.8A
Phase failure sensitive	1
Switch off technique	Thermomagnetic
Rated operating voltage	400...690V
Rated permanent current Iu	1,6A
Rated operation power at AC-3, 230 V	0,37kW
Rated operation power at AC-3, 400 V	0,37kW
Type of electrical connection of main circuit	Frame clamp
Device construction	Built-in device fixed built-in technique
With integrated auxiliary switch	
With integrated under voltage release	
Number of poles	3
Rated short-circuit breaking capacity Icu at 400 V, AC	100kA
Degree of protection (IP)	IP20

Desen cotat

