

MPE25-2,5



Specificatii

Cod ETI	004648007
Descriere	MPE25-2,5
Denumire clasă	Înterupător protec ie motor
P (AC3 kW) (kW)	0,75
Domeniul de setare al curentului (A)	1,6 - 2,5
Curent scurcircuit I _{rm} (A)	32,5
Tensiunea maxima de operare (V AC)	690

[Pagina de produse online](#)

Alta documentatie



[Catalog caracteristici tehnice](#)

[Model 3D](#)

[Manual de instructiuni](#)

[Declaratie CE](#)

[Eplan mușchi](#)

ETIM clasificare internationala

Clasificare	EC000074
Denumire clasă	Motor protection circuit-breaker
Overload release current setting	1.6...2.5A
Adjustment range undelayed short-circuit release	32.5...32.5A
Phase failure sensitive	1
Switch off technique	Thermomagnetic
Rated operating voltage	400...690V
Rated permanent current Iu	2,5A
Rated operation power at AC-3, 230 V	0,75kW
Rated operation power at AC-3, 400 V	0,75kW
Type of electrical connection of main circuit	Frame clamp
Device construction	Built-in device fixed built-in technique
With integrated auxiliary switch	
With integrated under voltage release	
Number of poles	3
Rated short-circuit breaking capacity Icu at 400 V, AC	100kA
Degree of protection (IP)	IP20

Desen cotat

