

MPE25-4,0



Specificatii

Cod ETI	004648008
Descriere	MPE25-4,0
Denumire clasă	Înterupător protec ie motor
P (AC3 kW) (kW)	1,5
Domeniul de setare al curentului (A)	2,5 - 4,0
Curent scurcircuit I _{rm} (A)	52
Tensiunea maxima de operare (V AC)	690

Pagina de produse online

Alta documentatie



Catalog caracteristici tehnice

Model 3D

Manual de instructiuni

Declaratie CE

Eplan mușchi

ETIM clasificare internațională

Clasificare	EC000074
Denumire clasă	Motor protection circuit-breaker
Overload release current setting	2.5...4.0A
Adjustment range undelayed short-circuit release	52...52A
Phase failure sensitive	1
Switch off technique	Thermomagnetic
Rated operating voltage	400...690V
Rated permanent current I _u	4A
Rated operation power at AC-3, 230 V	1,5kW
Rated operation power at AC-3, 400 V	1,5kW
Type of electrical connection of main circuit	Frame clamp
Device construction	Built-in device fixed built-in technique
With integrated auxiliary switch	
With integrated under voltage release	
Number of poles	3
Rated short-circuit breaking capacity I _{cu} at 400 V, AC	100kA
Degree of protection (IP)	IP20

Desen cotat

