

MPE25-10



Specificatii

| | |
|--|-----------------------------|
| Cod ETI | 004648010 |
| Descriere | MPE25-10 |
| Denumire clasă | Înterupător protec ie motor |
| P (AC3 kW) (kW) | 4,5 |
| Domeniul de setare al curentului (A) | 6,3 - 10 |
| Curent scurcircuit I _{rm} (A) | 130 |
| Tensiunea maxima de operare (V AC) | 690 |

Pagina de produse online

Alta documentatie



Catalog caracteristici tehnice

Model 3D

Manual de instructiuni

Declaratie CE

Eplan mușchi

ETIM clasificare internationala

| | |
|--|--|
| Clasificare | EC000074 |
| Denumire clasă | Motor protection circuit-breaker |
| Overload release current setting | 6.3...10.0A |
| Adjustment range undelayed short-circuit release | 130...130A |
| Phase failure sensitive | 1 |
| Switch off technique | Thermomagnetic |
| Rated operating voltage | 400...690V |
| Rated permanent current I _u | 10A |
| Rated operation power at AC-3, 230 V | 4,5kW |
| Rated operation power at AC-3, 400 V | 4,5kW |
| Type of electrical connection of main circuit | Frame clamp |
| Device construction | Built-in device fixed built-in technique |
| With integrated auxiliary switch | |
| With integrated under voltage release | |
| Number of poles | 3 |
| Rated short-circuit breaking capacity I _{cu} at 400 V, AC | 100kA |
| Degree of protection (IP) | IP20 |

Desen cotat

