

# MPE25-20



## Specificatii

Cod ETI	004648012
Descriere	MPE25-20
Denumire clasă	Înterupător protec ie motor
P (AC3 kW) (kW)	9,2
Domeniul de setare al curentului (A)	16 - 20
Curent scurcircuit I <sub>rm</sub> (A)	260
Tensiunea maxima de operare (V AC)	690

Pagina de produse online

## Alta documentatie



Catalog caracteristici tehnice

Model 3D

Manual de instructiuni

Declaratie CE

Eplan mușchi

## ETIM clasificare internationala

Clasificare	EC000074
Denumire clasă	Motor protection circuit-breaker
Overload release current setting	16.0...20.0A
Adjustment range undelayed short-circuit release	260...260A
Phase failure sensitive	1
Switch off technique	Thermomagnetic
Rated operating voltage	400...690V
Rated permanent current I <sub>u</sub>	20A
Rated operation power at AC-3, 230 V	9,2kW
Rated operation power at AC-3, 400 V	9kW
Type of electrical connection of main circuit	Frame clamp
Device construction	Built-in device fixed built-in technique
With integrated auxiliary switch	
With integrated under voltage release	
Number of poles	3
Rated short-circuit breaking capacity I <sub>cu</sub> at 400 V, AC	50kA
Degree of protection (IP)	IP20

## Desen cotat

