

LS32 SMA A2



Specificatii

Cod ETI	004660062
Descriere	LS32 SMA A2
Denumire clasă	Separator PV
Funcție	Separatoare de sarcina, 0-1
Număr de poli	2
Montare	Montat pe sina DIN
Curent termic I _{th} (A)	32
Tensiunea maxima de operare U _r (V)	1500
Curent nominal operational I _e DC-21 B la 1000V DC (A)	32

[Pagina de produse online](#)

Alta documentatie



[Catalog caracteristici tehnice](#)

[Model 3D](#)

[Manual de instructiuni](#)

[Declaratie CE](#)

[Eplan mușchi](#)

ETIM clasificare internațională

Clasificare	EC000216
Denumire clasă	Switch disconnector
Version as main switch	1
Version as maintenance-/service switch	1
Version as safety switch	1
Version as emergency stop installation	
Version as reversing switch	
Max. rated operation voltage Ue AC	440V
Rated operating voltage	300...1000V
Rated permanent current Iu	32A
Rated permanent current at AC-21, 400 V	32A
Conditioned rated short-circuit current Iq	5kA
Number of poles	2
Motor drive optional	
Motor drive integrated	
Voltage release optional	
Device construction	Built-in device fixed built-in technique
Suitable for floor mounting	
Suitable for front mounting 4-hole	
Suitable for front mounting centre	
Suitable for distribution board installation	1
Suitable for intermediate mounting	
Colour control element	Black
Type of control element	Turn button
Interlockable	
Type of electrical connection of main circuit	Frame clamp
Degree of protection (IP), front side	IP20