

ED2 400/3



Specificatii

Cod ETI	004671274
Descriere	ED2 400/3
Denumire clasă	Separator
Curent nominal (A)	400
Număr de poli	3
Categorie de utilizare	AC-23A, DC-22A
Standarde	IEC 60947-3
Tipul conexiunii	front connection
Tensiunea nominală de rezistență Uimp (kV)	8kV
Tensiunea nominală (V AC)	690
Tensiune nominală de izolare (V)	800V
Tensiune nominală de lucru (V DC)	250
Capacitate nominală de scurtcircuit Icm	9
Curentul de lucru la 0,3 s Icw	5

[Pagina de produse online](#)

Alta documentatie



[Catalog caracteristici tehnice](#)

[Model 3D](#)

[Declaratie CE](#)

[Eplan mușchi](#)

ETIM clasificare internațională

Clasificare	EC000216
Denumire clasă	Switch disconnector
Version as main switch	1
Version as maintenance-/service switch	1
Version as safety switch	1
Rated permanent current I _u	400A
Conditioned rated short-circuit current I _q	70kA
Number of poles	3
Motor drive optional	1
Voltage release optional	1
Device construction	Built-in device fixed built-in technique
Suitable for floor mounting	1
Type of control element	Rocker lever
Type of electrical connection of main circuit	Screw connection
Degree of protection (IP), front side	IP20