

EB2S 160/3HF 100A 3p



Specificatii

Cod ETI	004671861
Descriere	EB2S 160/3HF 100A 3p
Denumire clasă	Înterupător de circuit în car
Funcie	MCCB
Curent nominal (A)	100
Număr de poli	3
Standarde	60947
Tipul conexiunii	front connection
Tensiunea nominala de rezistenta Uimp (kV)	8
Tensiunea nominala (V AC)	690V
Tensiune nominala de izolare (V)	800
Capacitate nominala de scurtcircuit la 415 V Icu/Ics (kA)	40/20
Tensiune nominala de lucru (V DC)	250V
Reglare termica	fixed
Ajustare magnetica	fixed
Reglabil sau fix	Fix

[Pagina de produse online](#) 

Alta documentatie



[Catalog caracteristici tehnice](#)

[Model 3D](#)

[Manual de instructiuni](#)


[Declaratie CE](#)

[Eplan mușchi](#)

ETIM clasificare internationala


Clasificare	EC000228
Denumire clasă	Power circuit-breaker for trafo/generator/installation protection
Rated permanent current I _u	100A
Rated short-circuit breaking capacity I _{cu} at 400 V, 50 Hz	40kA
Overload release current setting	100...100A
Adjustment range undelayed short-circuit release	1500...1500A
Integrated earth fault protection	
Type of electrical connection of main circuit	Screw connection
Device construction	Built-in device fixed built-in technique
With switched-off indicator	1
Number of poles	3
Type of control element	Rocker lever
Motor drive integrated	
Motor drive optional	
Degree of protection (IP)	IP20

Caracteristici



Desen cotat

EB2S 160 F & A



EB2S 250 F & A

