

EB2 250/3H 160A 3p



Specificatii

Cod ETI	004672130
Descriere	EB2 250/3H 160A 3p
Denumire clasă	Înterupător de circuit în car
Curent nominal (A)	160
Număr de poli	3
Grup Catalog	EB2
Standarde	60947
Tipul conexiunii	front connection
Tensiunea nominala de rezistenta Uimp (kV)	8
Tensiunea nominala (V AC)	690V
Tensiune nominala de izolare (V)	800
Capacitate nominala de scurtcircuit la 415 V Icu/Ics (kA)	65/36
Tensiune nominala de lucru (V DC)	250V
Reglare termica	0,63-1
Ajustare magnetica	6-13
Reglabil sau fix	ajustabil

Pagina de produse online

Alta documentatie



Model 3D
 Manual de instructiuni
 Declaratie CE
 Eplan mușchi
 Catalog caracteristici tehnice

ETIM clasificare internationala

Clasificare	EC000228
Denumire clasă	Power circuit-breaker for trafo/generator/installation protection
Rated permanent current I _u	160A
Rated short-circuit breaking capacity I _{cu} at 400 V, 50 Hz	65/36kA
Overload release current setting	100.8...160A
Adjustment range undelayed short-circuit release	960...2080A
Type of electrical connection of main circuit	Screw connection
Device construction	Built-in device fixed built-in technique
With switched-off indicator	1
Number of poles	3
Type of control element	Rocker
Motor drive integrated	
Motor drive optional	1
Degree of protection (IP)	IP20

Caracteristici



