

ED2 1600/3 FC



Specificatii

Cod ETI	004672372
Descriere	ED2 1600/3 FC
Denumire clasă	Separator
Curent nominal (A)	1600
Număr de poli	3
Categorie de utilizare	AC-23A, DC-22A
Standarde	IEC 60947-3
Tipul conexiunii	extension bars
Tensiunea nominală de rezistență Uimp (kV)	8kV
Tensiunea nominală (V AC)	690
Tensiune nominală de izolare (V)	800V
Tensiune nominală de lucru (V DC)	250
Capacitate nominală de scurtcircuit Icm	45
Curentul de lucru la 0,3 s Icw	20

Pagina de produse online [🔗](#)

Alta documentatie



Catalog caracteristici tehnice

Model 3D

Declaratie CE

Eplan mușchi

ETIM clasificare internațională

Clasificare	EC000216
Denumire clasă	Switch disconnector
Version as main switch	1
Version as maintenance-/service switch	1
Version as safety switch	1
Rated permanent current I _u	1600A
Conditioned rated short-circuit current I _q	100kA
Number of poles	3
Motor drive optional	1
Voltage release optional	1
Device construction	Built-in device fixed built-in technique
Suitable for floor mounting	1
Type of control element	Rocker lever
Type of electrical connection of main circuit	Rail connection
Degree of protection (IP), front side	IP20