

ED2 1250/4



Specificatii

| | |
|--|----------------|
| Cod ETI | 004672381 |
| Descriere | ED2 1250/4 |
| Denumire clasă | Separator |
| Curent nominal (A) | 1250 |
| Număr de poli | 4 |
| Categorie de utilizare | AC-23A, DC-22A |
| Standarde | IEC 60947-3 |
| Tipul conexiunii | extension bars |
| Tensiunea nominală de rezistență Uimp (kV) | 8kV |
| Tensiunea nominală (V AC) | 690 |
| Tensiune nominală de izolare (V) | 800V |
| Tensiune nominală de lucru (V DC) | 250 |
| Capacitate nominală de scurtcircuit Icm | 32 |
| Curentul de lucru la 0,3 s Icw | 15 |

[Pagina de produse online](#) 

Alta documentatie



[Catalog caracteristici tehnice](#)

[Model 3D](#)

[Declaratie CE](#)

[Eplan mușchi](#)

ETIM clasificare internațională

| | |
|--|--|
| Clasificare | EC000216 |
| Denumire clasă | Switch disconnector |
| Version as main switch | 1 |
| Version as maintenance-/service switch | 1 |
| Version as safety switch | 1 |
| Rated permanent current I _u | 1250A |
| Conditioned rated short-circuit current I _q | 100kA |
| Number of poles | 4 |
| Motor drive optional | 1 |
| Voltage release optional | 1 |
| Device construction | Built-in device fixed built-in technique |
| Suitable for floor mounting | 1 |
| Type of control element | Rocker lever |
| Type of electrical connection of main circuit | Rail connection |
| Degree of protection (IP), front side | IP20 |